

CRF250X

Key Information

Category (ies)	Enduro
Price	R89 990
Product Name	CRF250X

General

Service intervals	As per owners manual
0 -- 100 km/h (sec)	N/A

Dimensions & Weights

Claimed KERB weight (kg)	115
Length (mm)	2174
Width (mm)	827
Height (mm)	1261
Seat height (mm)	815
Rake/trail (°/ mm)	N/A
WheelBase (mm)	1481

Drive

Drive	Chain
Front suspension	47mm inverted Showa leading-axle twin-chamber cartridge-type telescopic fork with 16-step adjustable compression and rebound damping; 280mm axle travel
Rear suspension	Pro-Link with single Showa damper, adjustable low-speed (13-step) & high-speed (3.5-turn) compression and 17-step rebound damping; 313mm axle travel

Engine

Tank capacity (l)	7.3
Starter	Electric/Primary kick
Fuel system	37mm Keihin FCR flat slide carburettor
Engine configuration	Liquid-cooled 4-stroke UNICAM 76° V4
Cylinders	1
Valves Per cylinder	4
Capacity (cc)	249
Power (KW)	21.9KW / 9,000 RPM
Torque (NM)	24.2NM / 8,000 RPM

Gearbox	5-spd
---------	-------

Safety

Brakes	(f) 240 x3mm hydraulic disc with dual-piston caliper and sintered metal pads, (r) 240x 4mm hydraulic disc with single-piston caliper and sintered metal pads
--------	--

Styling

Frame material	Semi-double cradle; aluminium twin-spar
----------------	---

Wheels

Tyres (f)	90/90-21
Tyres (r)	120/90-18
Wheels	Aluminium rim/wire spoke